



SPEEDOMAK

An ISO 9001 : 2008 Certified Company



Mobil Oil, Bike Engine Oil, Gear Oil, Hydraulic Oil, Brake Fluid & Greases





An ISO 9001 : 2008 Certified Company



WHOOPTM NLGI STANDARD
HIGHER DROP POINT 245° ABOVE
AP-L-RUN 30000 K.M.

PRODUCT DESCRIPTION

SPEEDOMAK WHOOP AP-L-RUN Grease is a multipurpose wheel bearing grease of outstanding performance suitable for use on all types of trucks, cars, farm equipments.

PRODUCT FEATURES

- Unique Transparent look & feel.
- Higher Drain Interval.
- Superior Wear & Corrosion protection.
- Unique adhesion/tacky protection.

PERFORMANCE STANDARD

Exceeds the requirements of AP-L-R NLGI-3.

CONSUMER BENEFITS

- Longer bearing life.
- Good mechanical stability and tenacity.
- Extreme pressure (EP) properties providing excellent load carrying characteristics.
- Excellent resistance to corrosion.

TECHNICAL DATA

Technical Specification	AP-L-R GREASE
Soap type	Lithium
NLGI Grade	3
Physical Structure	Red Crystal/Golden
Drop Point, °c min	245°C

STORAGE

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum marking. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.



Processed in India by :
SPEEDOMAK RUNNERS
243, Old Focal Point, Mehta Road,
Amritsar 143 001 INDIA



An ISO 9001 : 2008 Certified Company

PRODUCT DESCRIPTION

SPEEDOMAK Multipurpose Grease is a Calcium Soap Grease. Designed for general purpose lubrication. Also recommended for the lubrication of track rollers and idlers of certain Crawler type tractor.

PRODUCT FEATURES

- Unique Good lubrication.
- Golden Yellow Colour Processed is good characteristics base stock.
- Water Resistance properties.

CONSUMER BENEFITS

- Excellent water resistance.
- Lasting qualities in spring shackles and steering connection.
- Acts as protective layer on exposed parts.
- Clings to bearing surfaces.

TECHNICAL DATA

Free Acidity	-----
Soap type	Calcium
Free Alkalinity,	-----
Physical Structure	Golden Yellow
Drop Point, °c min	130°C

STORAGE

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum marking. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.





An ISO 9001 : 2008 Certified Company

PRODUCT DESCRIPTION

SPEEDOMAK CHASSIS Grease is a Calcium Soap Grease. Designed for general chassis lubrication. Also recommended for the lubrication of track rollers and idlers of certain Crawler type tractor.

PRODUCT FEATURES

- Unique Good lubrication.
- Dark Green Colour Processed is good characteristics base stock.
- Water Resistance properties.

CONSUMER BENEFITS

- Excellent water resistance.
- Lasting qualities in spring shackles and steering connection.
- Acts as protective layer on exposed parts.
- Clings to bearing surfaces.

TECHNICAL DATA

Free Acidity	-----
Soap type	Calcium
Free Alkalinity,	-----
Physical Structure	Dark Green
Drop Point, °c min	130°C

STORAGE

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum marking. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.





An ISO 9001 : 2008 Certified Company



Soluble Cutting Oils

PRODUCT DESCRIPTION

SPEEDOMAK Soluble Cutting Oil is a general purpose soluble cutting oils of the non-EP additive formulated by using mineral base oils, emulsifier and bactericide. This given stable milky emulsion on cutting operation. It helps wide range of metal working operations.

APPLICATION

SPEEDOMAK Soluble Cutting oil recommended for metal cutting, turning & boring, threading, drilling, shaping, grinding, milling operations on metal such as Copper, Bronze Brass. Aluminium and other alloys. Dilution condition depends on the nature and severity condition under operation.

CONSUMER BENEFITS

- Highly stable milky white emulsion used for machining ranges 3% to 4% depending severity of machining.
- No staining or discoloration, having excellent antirust properties.
- Suitable for most cutting operations on ferrous as well as non-ferrous metals.
- Causes no corrosion of machine, workpiece or tools.
- Prevent bacterial degradation or objectionable odor.
- Good precession with uniform hardness without metallurgical distortion for production requirements.



STORAGE

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum marking. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.



Processed in India by :
SPEEDOMAK RUNNERS
243, Old Focal Point, Mehta Road,
Amritsar 143 001 INDIA



An ISO 9001 : 2008 Certified Company

PRODUCT DESCRIPTION

SPEEDOMAK is tripple action long life radiator coolant prepared from selected ingredients to meet the highest Japanese standard and is free from Amines, Borates, Nitrates and Silicates and Phosphates.

APPLICATION

SPEEDOMAK is recommended for passenger cars, light commercial vehicles, heavy vehicles and heavy earth moving equipment as a radiator coolant. For desired performance 30 parts of the fluid is to be diluted with 70 parts of distilled water in most of the vehicles.

CONSUMER BENEFITS

- Does not boil and vaporise in the hottest summer or freeze in severe winter
- Prevents corrosion of radiator components and other parts.
- Increases cooling efficiency.
- Reduces maintenance costs and increase radiator life.

TECHNICAL DATA

PH of 30 v/v%Soln in distilled water	7.5-9.0
Specific Gravity @ 20°C. Min.	1.114
Freezing Point, °C	(-) 14
Physical Structure	Clear Fl. Green Liquid
Boiling Point, °c min	190°C

STORAGE

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum marking. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.





An ISO 9001 : 2008 Certified Company



Hydraulic Oils

PRODUCT DESCRIPTION

SPEEDOMAK Hydraulic Oils are high performance oil. These oil provide superior antiwear protection, excellent oxidation and thermal stability and good demulsibility. These oils provide problem free service and have been found to be far superior in performance compared to other commercially available antiwear, heavy duty hydraulic oils.

APPLICATION

SPEEDOMAK Hydraulic Oils are recommended as a fluid media in hydraulic systems, operating under extremely severe conditions. These oils are recommended for sophisticated high performance electro-hydraulic of numerically controlled systems. Hydraulic Oils are also recommended for lubrication of screw compressors requiring oil of excellent thermal stability where the components are silver or silver coated.

CONSUMER BENEFITS

- Ensure long service life due to outstanding oxidation and thermal stability.
- Provide sludge free high temperature performance.
- Provide excellent filterability characteristics.
- Readily separate from water because of excellent demulsibility characteristics.

COMPANY STANDARD

An ISO 9001 : 2008 Certified Company



STORAGE

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum marking. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.



Processed in India by :
SPEEDOMAK RUNNERS
243, Old Focal Point, Mehta Road,
Amritsar 143 001 INDIA



An ISO 9001:2008 Certified Company

PRODUCT DESCRIPTION

SPEEDOMAK Bike Engine oil is all season multi grade oil is suited for all types of 4-stroke motorcycles used in all driving conditions city, highway and off road.

FEATURE & DETAILS

SPEEDOMAK Bike Engine oil suitable for all types of 4 stroke bikes upto 150 cc.

Excellent operation at high temperature conditions high detergent and dispersant properties keep the engine, gear and wet clutch clean. Reinforced anti-wear ability extends engine life.

CONSUMER BENEFITS

- SPEEDOMAK 20W-40 is a value product that helps make your motorcycle ride trouble free.
- SPEEDOMAK 4T fully synthetic oil with Race Derived Technology minimizes friction, it is proven in motorsports and stays strong even at high speeds.
- It provides Ultimate Performance and Racing Acceleration
- SPEEDOMAK 4T with Power Release Formula provides Superior Acceleration at the touch of the throttle.

Product Range :
API SM 20w-40, API SL 20w-40



STORAGE

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum marking. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.





SPEEDOMAK

A Brand of Maharani Group of Companies

An ISO 9001 : 2008 Certified Company





SPEEDOMAK



Processed in India by :
SPEEDOMAK RUNNERS
243, Old Focal Point, Mehta Road,
Amritsar 143 001 INDIA

